


ST S

SLIP ON FLANGES

ANSI ASTM B16.5 A105



300LBS

IN.MM

		Raised face	Base Of hub	thick	Dia.of Bolt	Thru. hub	Bore		Dia.of Bolt	Approx Weight
	D	G	X	t	Circle	T2	B2		Holes	
size	In	In	In	In	In	In	In	No.of	In	Pounds
DN	mm	mm	mm	mm	mm	mm	mm	holes	mm	KG
½"	3.75	1.38	1.5	0.56	2.62	0.88	0.88	4	0.62	1.40
	95.3	34.9	38.1	14.2	66.7	22.4	22.4	4	16	0.64
¾"	4.62	1.69	1.88	0.62	3.25	1	1.09	4	0.75	2.50
	117.3	42.9	47.6	15.7	82.5	25.4	27.7	4	20	1.12
1"	4.88	2	2.12	0.69	3.5	1.06	1.36	4	0.75	3.00
	123.9	50.8	53.8	17.5	88.9	26.9	34.5	4	20	1.36
1 ¼"	5.25	2.5	2.5	0.75	3.88	1.06	1.7	4	0.75	3.70
	133.4	63.5	63.5	19.1	98.4	26.9	43.2	4	20	1.68
1 ½"	6.12	2.88	2.75	0.81	4.5	1.19	1.95	4	0.88	5.50
	155.4	73	69.9	20.6	114.3	30.2	49.5	4	23	2.49
2"	6.5	3.62	3.31	0.88	5	1.31	2.44	8	0.75	6.30
	165	92.1	84.1	22.4	127	33.3	62	8	20	2.87
2 ½"	7.5	4.12	3.94	1	5.88	1.5	2.94	8	0.88	9.50
	190.5	104.8	100	25.4	149.2	38.1	74.7	8	23	4.32
3"	8.25	5	4.62	1.12	6.62	1.69	3.57	8	0.88	12.90
	209.6	127	117.5	28.4	168.3	42.9	90.7	8	23	5.85
3 ½"	9	5.5	5.25	1.19	7.25	1.75	4.07	8	0.88	16.20
	228.6	139.7	133.3	30.2	184.1	44.5	103.4	8	23	7.34
4"	10	6.19	5.75	1.25	7.88	1.88	4.57	8	0.88	21.20
	254	157.2	146	31.8	200	47.8	116.1	8	23	9.61
5"	11	7.31	7	1.38	9.25	2	5.66	8	0.88	27.10
	279	185.7	177.8	35.1	234.9	50.8	143.8	8	23	12.30
6"	12.5	8.5	8.12	1.44	10.62	2.06	6.72	12	0.88	34.40
	317.5	215.9	206.4	36.6	269.9	52.3	170.7	12	23	15.60
8"	15	10.62	10.25	1.62	13	2.44	8.72	12	1	53.30
	381	269.9	260.3	41.1	330.2	62	221.5	12	26	24.20
10"	17.5	12.75	12.62	1.88	15.25	2.62	10.88	16	1.12	75.10
	444.5	323.8	320.7	47.8	387.3	66.5	276.4	16	29	34.10
12"	20.5	15	14.75	2	17.75	2.88	12.88	16	1.25	110.00
	520.7	381	374.6	50.8	450.8	73.2	327.2	16	32	49.80
14"	23	16.25	16.75	2.12	20.25	3	14.14	20	1.25	154.00
	584.2	412.8	425.5	53.8	514.3	76.2	359.2	20	32	69.90
16"	25.5	18.5	19	2.25	22.5	3.25	16.16	20	1.38	194.00
	647.7	469.9	482.6	57.2	571.5	82.6	410.5	20	35	88.10
18"	28	21	21	2.38	24.75	3.5	18.18	24	1.38	240.00
	711.2	533.4	533.4	60.5	628.6	88.9	461.8	24	35	109.00
20"	30.5	23	23.12	2.5	27	3.75	20.2	24	1.38	295.00
	774.7	584.2	587.4	63.5	685.8	95.3	513.1	24	35	134.00
24"	36	27.25	27.62	2.75	32	4.19	24.25	24	1.62	443.00
	914.4	692.2	701.7	69.9	812.8	106.4	616	24	42	201