



PN16

MM

DN	ISO	DIN	D	b	k	h1	d3	s	r	h2	d4	f	Bolt hole no.	d2	Appro. weight kg
15		20	95	14	65	35	30	2	4	6	45	2	4	14	0.648
	21.3	32													
20		25	105	16	75	38	38	2.3	4	6	58	2	4	14	0.952
	26.9	40													
25		30	115	16	85	38	42	2.6	4	6	68	2	4	14	1.14
	33.7	45													
32		38	140	16	100	40	52	2.6	6	6	78	2	4	18	1.69
	42.4	56													
40		44.5	150	16	110	42	60	2.06	6	7	88	3	4	18	1.86
	48.3	64													
50		57	165	18	125	45	72	2.9	6	8	102	3	4	18	2.53
	60.3	75													
65	76.1		185	18	145	45	90	2.9	6	9	122	3	4	18	3.06
80	88.9		200	20	160	50	105	3.2	8	10	138	3	8	18	3.7
100		108	220	20	180	52	125	3.6	8	10	158	3	8	18	4.62
	114.30	131													
125		133	250	22	210	55	150	4	8	10	188	3	8	18	6.3
	139.7	156													
150		159	285	22	240	55	175	4.5	10	12	212	3	8	22	7.75
	168.3	184													
175	193.7		315	24	270	60	210	5.4	10	12	242	3	8	22	9.85
200	219.1		340	24	295	62	235	5.9	10	16	268	3	12	22	11
250		267	405	26	355	70	285	6.3	12	16	320	3	12	26	15.6
	273	292													
300	323.9		460	28	410	78	344	7.0	12	16	378	4	12	26	22
350	355.6		520	30	470	82	390	8	12	16	438	4	16	26	31.2
		368					390								28.8
400	406.4		580	32	525	85		8	12	16	490	4	16	30	39.3
		419					445								36.3
500	508		715	34	650	90	548	8	12	16	610	4	20	33	61
600	610		840	36	770	95	652	8.8	12	18	725	5	20	36	75.4
700	711		910	36	840	100	755	8.8	12	18	795	5	24	36	77
800	813		1052	38	950	105	855	10	12	20	900	5	24	39	101
900	914		1125	40	1050	110	955	10	12	20	1000	5	28	39	122
1000	1016		1255	42	1170	120	1058	10	16	22	1115	5	28	42	162
1200	1220		1485	48	1390	130	1262	12.5	16	30	1330	5	32	48	243
1400	1420		1685	52	1590	145	1465	14.2	16	30	1530	5	36	48	323
1600	1620		1930	58	1820	160	1668	16	16	35	1750	5	40	56	479
1800	1820		2130	62	2020	170	1870	17.5	16	35	1950	5	44	56	599
2000	2020		2345	66	2230	180	2072	20	16	40	2150	5	48	62	919